

SKR series

- 105°C high-temperature resistance, high ripple current.
- RoHS Compliance.
- 105°C耐高温、高紋波。



SPECIFICATIONS

Items 項目	Characteristics 特性		
Capacitance Tolerance 靜電容量誤差	$\pm 20\%$ (120Hz,20°C)		
Operating Temperature Range 適用溫度範圍	-40 ~ +105°C		-25 ~ +105°C
Rated Voltage Range 額定電壓範圍	160 ~ 400VDC		450VDC
Leakage Current 洩漏電流	$I \leq 0.03CV + 20 (\mu A)$ (After 3 minutes application of DC rated voltage)		
Dissipation Factor 散逸因素($\tan \delta$)	Measurement Frequency: 120Hz. Temperature: 20°C Rated Voltage(V) 160~250 400~450 $\tan \delta$ (Max) 0.15 0.20		
Low Temperature Stability 低溫特性	Measurement Frequency: 120Hz. Rated Voltage(V) 160~250 400 450 $Z(-25^\circ C)/Z(20^\circ C)$ 3 5 6 $Z(-40^\circ C)/Z(20^\circ C)$ 6 6 -		
Load Life 負荷壽命	The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with the rated ripple current is applied for 2,000 hours at 105°C. Capacitance Change Within $\pm 20\%$ of Initial Value $\tan \delta$ 200% or less of Initial Specified Value Leakage Current Initial Specified Value or less		
Shelf Life 放置壽命	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours 105°C without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to them 4.1 of JIS C5101-4. Capacitance Change Within $\pm 20\%$ of Initial Value $\tan \delta$ 200% or less of Initial Specified Value Leakage Current Initial Specified Value or less		
Standards 參照標準	JIS C 5101-4 (IEC 60384)		

Frequency Coefficient of Permissible Ripple Current


Capacitance (μF)	Frequency (Hz)			
	120	1K	10K	100K
22~82	1.00	1.25	1.50	1.75
100~470	1.00	1.15	1.30	1.40

The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced.

SKR

SKR series

DIMENSIONS(mm)



STANDARD RATINGS

D×L(mm) ; R.C.(mA rms) at 105°C 120Hz.

Cap (μF)	V	160		200		250		400		450		
		Item	D × L	R.C.	D × L	R.C.	D × L	R.C.	D × L	R.C.	D × L	R.C.
22								10x30	260	10x35	280	
33								10x40	360	13x30	375	
39								10x45	405	13x35	415	
47								13x35	443	13x40	465	
56								13x40	510	14.5x30	465	
68	10x25	375	10x30	485	13x25	530	13x45	580	14.5x40	600	14.5x35	520
							14.5x30	580	16x35	600	16x30	520
82	10x30	485	10x35	528	13x30	595	14.5x40	635	16x40	650	18x32	650
100	10x35	528	10x40	615	16x25	650	14.5x45	690	18x36	700	18x32	690
120	10x40	615	10x45	710	16x32	715	16x40	810	18x40	820	18x36	810
150	10x45	710	13x35	780	16x35	860	18x40	940	18x45	990	20x40	1000
220	13x40	880	13x45	995	18x36	1120						
			14.5x35	995								
270	13x45	995	16x35	1150	18x40	1200						
330	16x35	1150	16x40	1320								
470	18x40	1270	18x45	1660								

※ 13mm may be replaced by 12.5mm upon customer's request.